



SFUND RECORDS CTR 2166-00983

December 22, 1986

Los Angeles County Department of Public Works Engineering Services Division Post Office Box 2418 Terminal Annex Los Angeles, California 90051

Attention: Mr. Carl Sjoberg

Subject: Ocean Technology, Inc. (OTI)

Underground Storage Tank 2835 N. Naomi Street Burbank, CA 91504

In accordance with the October 1984 County of Los Angeles Guidelines for Underground Storage of Hazardous Materials, OTI is submitting the enclosed underground tank investigation report. The report was prepared by our environmental engineering consultant, Harding Lawson Associates (HLA), and includes a summary of the site's history, geology, hydrogeology, and laboratory analyses of soil samples taken during the investigation.

The HLA report also describes the following activities undertaken to remove the underground tank.

- 1. March 1985: A 550-gallon underground storage tank used to store spent trichlorethane (TCA) and isopropyl alcohol (IPA) was emptied; plans were made to remove the tank according to proper regulatory protocol per recommendation of LACDPW.
- 2. September 1985: During tank removal process, the empty tank was accidentally punctured. An on-site representative of LACDPW ordered the tank placed back in the ground and covered. LACDPW subsequently requested investigation for possible underground leakage.

Mr. Carl Sjoberg Page 2 November 26, 1986

- 3. In October 1985, a consultant (Gregg and Associates, Huntington Beach, California) was retained to conduct a subsurface investigation. This initial investigation indicated that some TCA may have been present in the soil to a depth of 40 feet. The consultant recommended further action to characterize any contamination.
- 4. Later in October 1985, a second consultant, CH2M HILL of Newport Beach, California, was retained to continue the investigation. In November 1985, CH2M HILL submitted a proposed plan of action to OTI which was submitted to LACDPW for approval.
- 5. In February 1986, CH2M HILL bored and sampled soil to a depth of 82 feet. Analytical results from this boring taken within three feet of the first hole referred to in #3 above, revealed little or no TCA contamination.
- 6. In May 1986, HLA was retained to analyze the conflicting data and recommend a course of action that would satisfy regulatory requirements and protect public health. The HLA analysis concluded:
 - a. Soil conditions indicate any leakage would be confined to a very narrow vertical soil column.
 - b. Leakage volume is small based upon a comparison of material purchase and disposal records.
 - c. If leakage had been substantial, the HLA soil tests taken from around the tank and several feet directly underneath the tank would show high concentration of compounds.
 - d. The site hole should be secured by removing the tank, refilling the hole and sealing the surface to prevent surface water infiltration of the subsurface.
- 7. In September 1986, the tank removal plan submitted to LACDPW was approved and the tank removed. Sixteen samples of the excavated soil were taken using a photoionization detector (PID). Readings were between 0 to 5 units indicating low concentration of compounds. Two soil samples were also taken approximately three feet below the bottom of the tank crater. Laboratory analysis of both samples reveal extremely low readings of 5 to 10 milligrams/kilogram, thus corroborating the PID readings.



Mr. Carl Sjoberg Page 3 November 26, 1986

Based upon the above information, OTI believes there is sufficient evidence that deep vertical or horizontal migration of the compounds has not occurred and proposes it proceed with the following remedial action.

- a. Refill the excavation and compact in accordance with Burbank Fire Department regulations.
- b. Pave over compacted soil with concrete and asphalt.

Presently, the excavation is covered with lumber and water impermeable plastic sheets to minimize the possibility of surface water migration. Signs have been posted to keep employees out of the area.

OTI appreciates your cooperation and understanding during this project. Once we receive your approval of the remedial action, OTI is prepared to proceed with its implementation. Should you have any questions or comments, OTI and HLA are willing to meet with you at your convenience.

Very truly yours,

OCEAN TECHNOLOGY, INC.

Eugene Palic Plant Engineer

EP:wp



Marding Lawson Associates

December 22, 1986

17876,001.11



Ocean Technology, Inc. 2835 North Naomi Street Burbank, California 91504

Attention: Mr. Gene Palic

Gentlemen:

Conclusions and Recommendations Underground Tank Investigation 2835 North Naomi Street Burbank, California

This letter provides conclusions and recommendations for Harding Lawson Associates' (HLA) report to Ocean Technology, Incorporated (OTI) entitled "Underground Tank Investigation, 2835 North Naomi Street, Burbank, California," dated November 24, 1986.

The following conclusions and recommendations are presented separately from our report in order to emphasize that the subject report was written to present data only. Our conclusions and recommendations are based on HLA field investigations, OTI's records, and unverified data obtained by other consultants previously involved in the project. A review of the data that we obtained for our report suggests the following general conclusions:

- 1. Some seepage from the tank has occurred in the past.
- 2. OTI's inventory records indicate that the volume of leakage was probably less than 200 gallons. Laboratory tests of soil samples taken by HLA from directly beneath the tank tend to support the conclusion that the amount of leakage was relatively small.
- 3. Boring logs indicate that the soils beneath the tank are granular and permeable. This would cause seepage beneath the tank to migrate primarily vertically with limited lateral spreading. Therefore, seepage from the tank is probably limited to a relatively narrow, vertical column.
- 4. Laboratory analyses of soil samples taken from three borings close to the tank indicate soils have been affected by seepage of halogenated volatile organic compounds to a depth of 30 to 40 feet.

December 22, 1986 17876,001.11 Mr. Gene Palic Ocean Technology, Inc. Page 2

Organic compounds were not detected in samples from 50 and 70 feet below the tank. Existing literature indicates ground water is approximately 185 feet deep in the area. We believe there is little likelihood that tank seepage has migrated to ground water.

We understand that OTI will submit this letter with our data report to the County of Los Angeles Department of Public Works for their review. In addition, we recommend that OTI request approval from the County of Los Angeles for the following additional actions:

- 1. Backfill the open pit with approved, compacted soil according to Burbank Fire Department regulations.
- Pave the backfilled tank pit to prevent infiltration of surface water, decreasing the potential for downward migration of contaminants.

We would be pleased to answer any questions that you may have regarding these conclusions and recommendations.

Very truly yours,

HARDING LAWSON ASSOCIATES

Gary J. Halbert, C.E.G. 1318

Senior Hydrogeologist

Donald A. Pape, C.E.G. - 1190

Associate Hydrogeologist

GJH/DAP/slb

Harding Lawson Associates

Engineers, Geologists & Geophysicists



UNDERGROUND TANK INVESTIGATION 2835 NORTH NAOMI STREET BURBANK, CALIFORNIA

HLA Job No. 17876,001.11

A Report Prepared for

Ocean Technology, Inc. 2835 North Naomi Street Burbank, California 91504

UNDERGROUND TANK INVESTIGATION 2835 NORTH NAOMI STREET BURBANK, CALIFORNIA

HLA Job No. 17876,001.11

by

Gary J. Halbert, C.E.G. - 1318

Senior Hydrogeologist

Donald A. Pape, C.E.G. - 1190

Associate Hydrogeologist

Harding Lawson Associates 15621 Redhill Avenue, Suite 100 Tustin, California 92680 714/259-7992

November 24, 1986

INTRODUCTION

This report presents the results of a soil investigation conducted during the removal of a 550-gallon underground storage tank at Ocean Technology, Inc. (OTI) facilities located at 2835 North Naomi Street in Burbank, California (Plate 1). The investigation was performed by Harding Lawson Associates (HLA) and was authorized by OTI through HLA's Service Agreement, dated May 20, 1986.

BACKGROUND

General

The Burbank OTI property was acquired from Hydraulic Research Corporation (HRC) in July, 1973. The site is located in an industrial area at the eastern margin of the San Fernando Valley. The subject facilities are used by OTI primarily for design and assembly of electronic components.

Burbank Fire Department records indicate a 550-gallon underground tank was installed by HRC in 1965 for storage of machine cutting oil. OTI records indicate the tank has been used to store waste 1,1,1-Trichloroethane (TCA) and isopropyl alcohol (IPA) since OTI occupied the property. According to documented

manifests, reportedly on file with OTI, the tank was emptied four times; in 1977, 1979, 1981, and 1985. OTI's inventory summary (Appendix A) gives a breakdown of the purchase, usage, and disposal of 1,1,1-Trichloroethane and Isopropyl Alcohol from 1977 to 1985.

We understand that, in an effort to comply with Los Angeles
County Department of Public Works (LACDPW) guidelines for underground storage of hazardous materials (enacted October 1984),
OTI has undertaken the following:

- 1. In March 1985, the 550-gallon underground storage tank was emptied and sealed by the Oil Process Company of Los Angeles. Plans were made to remove the tank according to then-existing regulatory guidelines.
- 2. In September 1985, during the initial tank removal attempt, the empty tank was accidentally punctured. A representative of LACDPW, on site during removal, ordered the tank left in the ground and covered. LACDPW subsequently requested an investigation for possible underground leakage.
- 3. In early October 1985, a consultant (Gregg and Associates, Huntington Beach, California) conducted a subsurface investigation. The investigation included two 40-foot-deep borings and laboratory analyses of soil samples. A report by Gregg and Associates describing that work has been provided to LACDPW by OTI. The boring logs and laboratory results from that report are included for reference in Appendices B and C, respectively.
- 4. Later in October 1985, a second consultant, CH2M HILL of Newport Beach, California, was retained to continue the investigation. In November 1985, CH2M HILL provided a proposed plan of action to OTI which was submitted to LACDPW.

.)

5. In February 1986, the work plan proposed by CH2M HILL was partially implemented by drilling and sampling one soil boring to a depth of 82 feet. A report describing the results of that work was not prepared. Draft copies of the CH2M HILL boring log and results of laboratory analyses soil samples are included for reference in Appendices B and C, respectively.

SCOPE OF WORK

In May 1986, HLA was retained by OTI to:

- Review existing data and reports pertaining to site conditions and the history of the subject tank,
- Assist OTI in arranging to have the tank removed,
- 3. Be present during tank removal to observe the condition of the tank and surrounding soils and to collect soil samples for laboratory analysis for volatile organics, and
- 4. Prepare this report.

Crosby and Overton/EMI (C&O/EMI) of Garden Grove, California was contracted by OTI to prepare a work plan and to remove the tank.

FIELD ACTIVITIES

The tank-removal work plan was approved by the LACDPW and the tank removal by C&O/EMI on September 26, 1986. A representative of the Burbank Fire Department was present during tank

removal. Mr. Joe Biacco of LACDPW was notified of the tank removal, but declined to attend.

An HLA geologist was present during the tank removal to record observations and take soil samples. Soil overlying the tank was excavated with a backhoe. The backhoe was used to remove the tank. Excavated soil was monitored with a photo-ionization detector (PID) equipped with a 10.2 million electron volt lamp calibrated against a benzene standard.

Two soil samples were collected from the excavation using the backhoe. One sample was selected from immediately beneath the tank at about 6 feet below original ground surface (Sample S-1); and another from 2 feet beneath the tank at about 8 feet below ground surface (Sample S-2).

The samples were placed in sealed glass jars, stored in a cooler with "Blue Ice," and delivered that day to Brown and Caldwell Laboratories in Pasadena, California.

The excavated soil (approximately 15 cubic yards) was left in a covered pile near the tank excavation.

SITE CONDITIONS

General

The geology and ground-water conditions at the site have been described in the November 1985 Proposed Plan of Action

prepared by CH2M HILL. Briefly, the site is located in an industrial area at the eastern margin of the San Fernando Valley Ground Water Basin. The site is underlain by several hundred feet of Quaternary-age, granular alluvium. Existing literature indicates that unconfined ground water is approximately 185 feet below the ground surface, and that ground water in this area flows to the south 1.

According to CH2M Hill, no active ground-water extraction wells are located within 1 mile of the site. One 2-inch-diameter monitoring well, maintained by LACDPW (Well No. 4969B), is located approximately 1000 feet south of the site.

Site Soils

A site plan is shown on Plate 2. The two boring logs (OTI-B-1 and OTI-B-2 in Appendix B) from the October 1985 Gregg and Associates report indicated soils beneath the paved tank area consist of silty sand to a depth of at least 6 feet, underlain by sand with little fines to a depth of 40 feet.

A <u>draft</u> copy of the field log of the CH2M HILL Boring B-3 was provided to HLA by OTI (included in Appendix B). The log indicates silty sand to a depth of 5 feet with sand, gravel, and

^{1.} County of Los Angeles Case No. 650079, "Water Master Service in the Upper Los Angeles River Area", 1984.

cobbles extending from 5 feet to the bottom of the boring at 82 feet.

HLA's observations during tank removal in September 1986 indicate that the tank backfill consisted of moist, brown, silty sand with cobbles. The tank backfill appeared to be the same as natural soils surrounding the tank pit. The soils around the tank had a moderate solvent or alcohol odor with PID readings of 0 to 5 units.

Tank Condition

During the September 1986 tank removal, HLA observed that the empty tank was in a deteriorated state. The tank had several large holes, from damage during an earlier backhoe removal attempt (September 1985). The tank was finally removed in dismembered sections.

The tank was also deteriorated from corrosion. Mr. Lou Stone of the Burbank Fire Department commented that the tank appeared to be more corroded than when he observed it during the first removal attempt in September, 1985.

Laboratory Analysis

HLA soil samples S-1 and S-2, taken from beneath the tanks, were analyzed for volatile organics and isopropyl alcohol by EPA

Method 8240. The results of analyses are presented in Table 1.

Laboratory test reports are given in Appendix C.

Table 1. Laboratory Results

	Concentration (mg/kg)		
	<u>s-l</u>	S-2	
1,1,1-Trichloroethane	5	6	
C-3 chlorinated hydrocarbon	8	10	


Notes: mg/kg = milligrams per kilogram only constituents that were detected are listed

Both samples showed two compounds above detectable limits: 1,1,1-Trichloroethane (TCA) and an undifferentiated C-3 chlor-inated (non-priority pollutant) compound. Isopropyl alcohol was not detected.

For reference, the previously-unreported results of laboratory analyses of samples from CH2M HILL Boring B-3 are included in Appendix C. Samples from 30 feet, 50 feet, and 70 feet were analyzed for oil and grease (EPA Method 418.1), isopropyl alcohol, and purgeable priority pollutants (EPA Method 8010). In summary, three analytes were detected in the 30-foot sample, whereas none of the analytes were detected in the two deeper samples. The three compounds detected at 30 feet were: oil and grease (170 mg/kg), isopropyl alcohol (140 mg/kg) and acetone (140 mg/kg).

Also included for reference in Appendix C is a copy of the results of laboratory analyses performed on soil samples taken from Borings OTI-B-1 and OTI-B-2. The laboratory report and the consultant's summary were excerpted from Gregg and Associates' report (dated October 21, 1985) which we understand is on file with appropriate regulatory agencies. The samples were analyzed for purgeable priority pollutants by EPA method 8010. Only TCA was reported. Briefly, a composite soil sample from OTI-B-1 contained 0.0007 mg/kg TCA. TCA was detected at 6.2 mg/kg at 5 feet, 12 mg/kg at 10 feet, and 520 mg/kg at 30 feet. The remaining samples at 15, 20 and 40 feet were all reported as less than 1 mg/kg TCA.

ILLUSTRATIONS





Harding Lawson Associates Engineers, Geologists & Geophysicists

Ocean Technology, Inc. Burbank, California

1


DRAWN JOB NUMBER 11 17876,001.11

APPROVED H

10-31-86

REVISED

DATE





Engineers, Geologists & Geophysicists

Ocean Technology, Inc.

Burbank, California

10-31-86

REVISED

_

DRAWN 11

JOB NUMBER 17876,001.11 LAPPROVED H

1-86

DATE

Harding Lawson Associates

المي سأ

APPENDIX A

OTI Chemical Purchase/Disposal Analysis

.

De artmental Correspondence

Date 9 June 1986

V. Spaccia V. Spaccia

Subject: CHEMICAL PURCHASE/DISPOSAL ANALYSIS

The following figures are a breakdown of the purchase, usage and disposal of the chemicals Trichlorethane 1.1.1 and Isopropyl Alcohol during the period from 7/01/77 to 4/17/85. All records prior to this time have been destroyed.

Trichlorethane 1.1.1:

Total Purchased	3,350.00 gal.
Total Usage (48.15%)	1,612.94 gal.
Balance	1,737.06 gal.

Isopropyl Alcohol:

Total Purchased	1,199.00 gal.
Total Usage (72.72%)	871.97 gal.
Ralance (Waste)	327.03 gal.

Combined Results:

Trichlorethane 1.1.1	1,737.06 gal.
Isopropyl Alcohol	327.03 gal.
	
Total Possible Storage	2,064.09 gal.
Actually Disposed Of	1,950.00 gal.
Seepage Loss	114.09 gal.

The percentage breakdown of the disposed chemicals (recycled) is 84.16% Trichlorethane 1.1.1 and 15.84% Isopropyl Alcohol. The gallon equivalent of that would be 96.02 gallons of Trichlorethane 1.1.1 and 18.07 gallons of Isopropyl Alcohol.

PUT IT IN WRITING: WRITTEN MESSAGES SAVE TIME AND AVOID ERRORS

APPENDIX B

PROJECT NUMBER

N20391, BO

3

SHEET 2 OF 4

SOIL BORING LOG

LOCATION BURDANK

LEVATION ______ DRILLING CONTRACTOR GREGG DRILLING & TOSTING

OBJULING METHOD AND EQUIPMENT HOLOW STOM AUGBR

				IIPMENT	Horrow >	Tom Auger		
w	ATER LEVE				STANDARD	START FINISH		LOGGER D. MARK
			SAMPLE		PENETRATION	SOIL DESCRIPTION		COMMENTS
ELEVATION	DEPTH BELOW SURFACE	INTERVAL	TYPE AND NUMBER	RECOVERY	TEST RESULTS 6"-6"-6" (N)	NAME, GRADATION OR PLASTICITY, PARTICLE SIZE DISTRIBUTION, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY, USCS GROUP SYMBOL	SYMBOLIC	DEPTH OF CASING DRILLING RATE. DRILLING FLUID LOSS. TESTS AND INSTRUMENTATION
	35'-		3-40	L c\0	34 blows A	same material - slightly higher 70 silt (still < 5%). More consolidated with depth, but still very little internal cohesion. few cabbles very few cobbles Fine- coarse sand with fewer peobles (2-3%). Well sorted - (2-3% silt clay	0.0	Easy drilling-occasional -
	45' -					very few cobbles.	. 0	
	. 4					more cobbles	0.	-
	<i>5</i> 0' -					Fine-coarse sand with 3-5% pebbles and occasional cobbles. Mostly ned. sand. Moderately sorted - higher siltand clay fraction (max. 5%). Slightly moist.	0-1-0-1	cobbles significantly increased bow count and inhibit ability to get drive sample.
	55'-					occasional cobbles.	0	
						more cobbles and pebbles	00	-
	60' -		3-60	Lab	40 Yours/C+	-see next page		AEV 11/82 FORM 01586

						PROJECT NUMBER	BORING NUMBER				
	Å	7			1		3		2		
Ail					}	3/461 3 05 4					
SOIL BORING LOG									G		
JA	OJECT _	OT	1				ATION BURBON				
	EVATION -					DRILLING CONTRACTOR GROSS					
		THOD A	ND EOL	JIPMENT		STOM AUGUR		3			
	TER LEVE						NISH		LOGGER D. MARK		
ſ			SAMPL		STANDARO	SOU DESCRIPTION					
z			Ī	-	PENETRATION TEST	·			COMMENTS		
ELEVATION	1 30	\ \ \	TYPE AND	RECOVERY	RESULTS	NAME, GRADATION OR PLA PARTICLE SIZE DISTRIBUTION		SYMBOLIC LOG	DEPTH OF CASING. DAILLING RATE		
	DEPTH BELOW SURFACE	NTERVAL	YPE	3	6"-6"-6" (N)	MOISTURE CONTENT, RELATIVE OR CONSISTENCY, SOIL STR		S C B	DRILLING FLUID LOSS TESTS AND		
=		Z Romor s	ΕŽ	<u>"</u>		MINERALOGY, USCS GROUP SY		8 7	INSTRUMENTATION		
- 1	_	17.				silty very fine to fine sa	nd, Moist -		still drilling casy		
						cohesive. Very little cky (< 1%). T		≈ 2'/minute		
- }	_	,		}	}	Few pebbles (170).	4	• • •			
ł	-			}			4		-		
I	-		}			3	4.				
j	65'-			1		DAF		•			
j			,	}	}	DRAFT	_ <u>}</u> _		_		
ł	4			ł	}		4.	<u>. </u>	-		
- 1	4			l			-{	· · · · σ	-		
ł	4				1		4		, .		
- }	j]		<u>}</u> :	<u> </u>			
- 1	70'-	{					7	•	•		
	10 -		3-70	Lab	35 Hours/A	silty very fine to fine sand coarser). Moist - cohesive. Lit (41-270), Few small peobles. Si	(blightly		-		
- 1	1					(coarser). Moist - cohesive. Lit	the clay				
	4	ST SEE				that (previously med, homes - dry	in to light brown	•			
- {			3-72	Kunnt	55 April 25	tint (previously med. brown - dry			_		
- {					}	1					
- {						cuttings: mostly pebbles with	tine sanc to	Tree.	Very hard drilling-rig		
	75' -	3.5	3-75	Leb	70 blows/	and silt matrix. More moist			chattering. Very slow		
- 1	4	415.00			Itzin.		-{		≈ <1'/k̄c		
- [4	,						0.0	very little muterial retrieved		
ı	اِ	ļ			}		j		in 75' dave sample.		
1]						1	0 (Slightly easier drilling at 76		
Ì	. 1	ł		}			+	\sim	-		
	80'-	of claims	20-	}	2-11 /2	lean a 1 - d nobbles	Little -	٠. c			
1	إ		3-80	لدل	140 promett	coarse sand and pebbles silt (<5%). Numerous cobb	oles.	C	-		
}		}	ļ. 	}		SIT (>) (0), NOTE (0)		•	-		
- {	ł				i		1				
	7	{			}	}	7:		·		
	- ,-			1	1		4	0.	•		
- }	85'-			ļ		Boulders			very slow drilling-beulders		
	4	}		}		10001000 3	4				
					Ì	}			@ 87 part of pad supporting		
- 1	}				[7		and colleges - tere excerance		
1	7	1			}		7		not properly buckfilled, Had		
}	, 1				}	}	4	1	Lost 2'of hole and kinge builder		
L	10.		L				4		cases into hele.		
						<u> </u>			REV 11/82 FORM 01585		

		J'			لز)	
	Å				i	N20391. BO	BORING NUM	BEA	SHEET 4 OF 4
	Mil				-		IL BORIN	GIO	
j						50	AL BURIN	G LO	J.
PROJECT OTI									
EL	EVATION					DAILLING CONTRACTOR _GR	GGG DRILLING	5 ¢ T8	STING
	ILLING ME TER LEVEI			•	HOLLOW	STEM AUGGR	FINISH		LOGGER D. MARK
			SAMPLE		STANDARD PENETRATION	SOIL DESCRIPTI			COMMENTS
NO.	w	بـــــــــــــــــــــــــــــــــــــ	9_	ž.	TEST RESULTS	NAME, GRADATION OR		ပ္	DEPTH OF CASING
ELEVATION	DEPTH BELOW SURFACE	INTERVAL	TYPE AND NUMBER	RECOVERY	6"-6"-6" (N)	PARTICLE SIZE DISTRIBUT MOISTURE CONTENT. RELA OR CONSISTENCY. SOIL MINERALOGY USCS GROU	TIVE DENSITY STRUCTURE.	SYMBOLIC	DRILLING RATE, DRILLING FLUID LOSS, TESTS AND INSTRUMENTATION
									No progress in 1 hr+
-						•]	Borehole abandoned.
]	•			}]	Backfilled hole with
]]	"5-suck mix"
- {]							_]	Soil samples taken to lab (Brown & Caldwell)
						_		7	(ab (Brown & Calowell)
	1					957		7	
	1				1	DRAFT		7	
I	1					DIV.		7	
	٦							1	
İ								7	_
	7				[1	
	1				}			1	
1	1							1	,
	4							1	
	7							7	-
ł	1								
	1				1			1	
1	4				}			1	
- 1	1							1	
	4							7	-
-	4							7	
-	1							=	
1	. 1							4	
1	4							1	
	4							4	-
	4				`			+	
- [4							+	
	4							-	
1	4							+	
J	1		1		1			4	

Harding Lawson Associates

APPENDIX B

Boring Logs
OIT-B-1, OTI-B-2, Gregg and Associates, November 1985
B-3 CH2M HILL, February 1986 (Draft)

٠

<i>y</i> .		•		<u>) </u>	PESCRIPTION
NSTRUCTION DETAILS	DEPIH	LOG	BLOV	LITHO!	
Gastech (ppm)	- 0 - - 3 - - 6 -	ないがか	5	-Asphall -Silty	inches
23	- 9 - - 12 -		23		(ine to coarse
17	- 15 -		17	-Sand gral"	hansity
18	- 18 - - 21- - 24 -		25	dense -Incre occa	, lansity , pebbles
O	- 27 - - 30 - - 33 - - 36 -		50+	-Samp!", atter/, use/!	retained in 4 auger cuttings ample
0	- 39 - 42		40+	-Sand, grai/, dens	(ine to coarse
COMPLETION & BACKFILL - Fackfilled native material, 0-40 ft				B/,	, NUMBER OTIBL
	·				indologies, inc.

)		4		RIPTION
NSTRUCTION DETAILS	DEPTH LOG	BLOW	LITHOLOGII'	
Gastech (ppm)	- 0 - 37.5% - 3 - - 6 -	7	-Asphalt, -Sand, sp, light bro -Silty sand, to med g!	ine to pebbles
500+	- 9 - - 12 -	15	and cobb	bles and
500+	- 15	36	-Sand (sp)	, to dark ,.llum dens
7300+	- 18 - 21-	40	pebbles, brown, modestrong of	
500+	- 24 - 27 - 30 - 33 - 36	80+	·	· .
500+	- 39 - 42	45		
	: "			-
		1		
COMPLETTON & BACKFILL —				HER OTIB2
Juckfilled concrete and renkonite, 0-40 ft			BORING	•
			·	s for
	•	-	Prep OCEAN TECF	, LATES, I

GREGG &

PROJECT NUMBER

BC. 1G .SMBER

N20391, BO

SHEET | OF 4

SOIL BORING LOG


PAOJECT DRILLING CONTRACTOR GREGG DRILLING & TESTING ELEVATION HOLLOW STEM AUGER - MOBILE DRILL MOBEL DRILLING METHOD AND EQUIPMENT_ LOGGER D. MARK 0940 WATER LEVEL AND DATE STANDARD COMMENTS SOIL DESCRIPTION SAMPLE ENETRATION TEST DEPTH OF CASING. NAME, GRADATION OR PLASTICITY. RESULTS RECOVERI DEPTH BELOW Surface PARTICLE SIZE DISTRIBUTION, COLOR, DRILLING RATE NTERVA 6"-6"-6" MOISTURE CONTENT, RELATIVE DENSITY DRILLING FLUID LOSS IN OR CONSISTENCY, SOIL STRUCTURE. TESTS AND INSTRUMENTATION MINERALOGY, USCS GROUP SYMBOL Moist bilty fine-medium sand. Drilling easy. briller indicates sal was very dry the last time he dilled at site. Moisture DRAFT apparently due to open excavation above tank and 5 recent rains. med.-coarse sand with pebbles. Fairly clean - little silt & cky 10' med. - occrse sand with peoples and o slower drilling due to 5-3-10 طم cobbles. Very little silt and cky. Slightly moist, but little internal cohesion due 21 Wows/ft cobbles. Faster drilling-fewer cobbles to large grain size. @ 10 1/2 numerous cobbles. Fewer cobbles after = 12' 15 20' 20 blows At | med - coarse sand with \$ 5-10% pebbles Fairly easy drilling 3-20 lab and occasional cobble. Maderately well except when run into sorted - little silt and clay (silt and c0/6400 clay combined < 5%). Slightly damp. 25 occasional cobble constant drilling rate slower drilling 28-29' more cobbles ecsier drilling 30 21 blows It - see next page REV 11/82 FORM DISES

Harding Lawson Associates

APPENDIX C

Laboratory Analyses

S-1, S-2, Harding Lawson Associates, September 1986 B-3 CH2M HILL, February 1986 OTI-B-1, OTI-B-2, Gregg and Associates, October 1986



ANALYTICAL LABORATORIES

LOG NO: P86-09-546

Received: 26 SEP 86 Reported: 14 OCT 86

Gary Halbert Harding Lawson Associates 15621 Redhill Ave., Suite 100 Tustin, California 92680

Project: 17876,001.11

REPORT OF ANALYTICAL RESULTS

Page 1

SAMPLE DESCRIPTION, SOIL SAMPLES		DA	TE SAMPLED
S-1			26 SEP 86 26 SEP 86
	09-546-1		
Priority Pollutants chloroethane, mg/kg etrachloroethane, mg/kg chloroethane, mg/kg croethane, mg/kg croethane, mg/kg croethane, mg/kg cropropane, mg/kg cropropene, mg/kg cropropene, mg/kg crile, mg/kg crile, mg/kg cremethane, mg/kg cremethane, mg/kg creme, mg/kg	10/09/86 5 <0.3 <0.3 <0.3 <0.3 <0.3 <0.3 <0.3 <0.3	6 <0.3 <0.3 <0.3 <0.3 <0.3 <0.3 <0.3 <0.3	
roethylene, mg/kg	<0.3	<0.3	
	S-1 S-2 Priority Pollutants Chloroethane, mg/kg Chloride, mg/kg Trachloroethane, mg/kg Trocthane, mg/kg Trocthane, mg/kg Trocthane, mg/kg Trocthane, mg/kg Trocthane, mg/kg Tropropane, mg/kg Tropropane, mg/kg Tropropene, mg/kg Tropropene, mg/kg Tropropene, mg/kg Tropropene, mg/kg Tropropene, mg/kg Trochloride, mg/kg Trachloride, mg/kg	S-1 S-2 O9-546-1 Priority Pollutants Chloroethane, mg/kg Chloroethane, mg/kg Chloroethane, mg/kg Chloroethane, mg/kg Chloride, mg/kg O9-546-1 O9-54	S-1 S-2 Priority Pollutants Chloroethane, mg/kg Chloride,

Received: 26 SEP 86 Reported: 14 OCT 86

Gary Halbert
Harding Lawson Associates
15621 Redhill Ave., Suite 100
Tustin, California 92680

Project: 17876,001.11


REPORT OF ANALYTICAL RESULTS

Page 2

LOG NO	SAMPLE DESCRIPTION, SOIL SAMPLES			TE SAMPLED
09-546-1 09-546-2	S-1			26 SEP 86 26 SEP 86
PARAMETER		09-546-1	09-546-2	
Trichlorof Toluene, m Vinyl Chlo trans-1,2- trans-1,3-	ethylene, mg/kg fluoromethane, mg/kg mg/kg oride, mg/kg Dichloroethylene, mg/kg Dichloropropene, mg/kg Alcohol, mg/kg	<0.3 <0.3 <0.3 <0.3 <0.3 <0.3	<0.3 <0.3 <0.3 <0.3 <0.3 <0.3	
	rified Results ** orinated Compound, mg/kg	8	10	

** Quantification based upon comparison of total ion count of the compound with that of the nearest internal standard.

Edward Vilson, Laboratory Director



CH2M HILL SOUTHERN CALIFORNIA OFFICE

- LOG NO: P86-02-030

Received: 03 FEB 86 Reported: 10 FEB 86

John Dolegowski CH2M.HILL 1301 Dove Street, Suite 800 Newport Beach, California 92660

Project: N20391.BO

LOG NO	SAMPLE DESCRIPTION , SOII	SAMPLES	DATE SAMPLED
02-030-1	B-3-30		03 FEB 86
PARAMETER		02-030-1	
	by Infrared, mg/kg Lcohol, mg/kg	170 140	

Received: 03 FEB 86 Reported: 10 FEB 86

John Dolegowski CH2M.HILL 1301 Dove Street, Suite 800 Newport Beach, California 92660

Project: N20391.B0

REPORT OF ANALYTICAL RESULTS

LOG NO	SAMPLE DESCRIPTION , SOIL SAMPLES		DATE SAMPLED
02-030-1			03 FEB 86
PARAMETER			
EPA Method			
Date Extr	racted	02/07/86	
1,1,2,2-1	etrachloroethane, mg/kg	<0.3	
1,1,2-Tri	chloroethane, mg/kg	<0.3	
1,1-Dichl	oroethane, mg/kg	<0.3	
1,1-Dichl	oroethene, mg/kg	(0.3	
1,2-Dichl	oroethane, mg/kg	<0.3	
trans-1,2	?-Dichloroethene, mg/kg	(0.3	
1,2-Dichloropropane, mg/kg		(0.3	
2-Chloroethylvinylether, mg/kg		(0.3	
Bromodichloromethane, mg/kg		⟨0.3	
Bromometh	nane, mg/kg	<0.3	
Bromoform	ı , m g/kg	<0.3	
Chloroben	nzene, mg/kg	(0.3	
Carbon Te	trachloride, mg/kg	(0.3	
Chloroeth	nane, mg/kg	(0.3	
Chlorofor	ma, mag/kg	<0.3	
Chloromet	hane, mg/kg	(0.3	
Dibromoch	nloromethane, mg/kg	(0.3	
Dichlorod	lifluoromethane, mg/kg	(0.3	
Methylene	chloride, mg/kg	<0.3	
Tetrachlo	proethene, mg/kg	(0.3	
	ichloroethane, mg/kg	(0.3	

Received: 03 FEB 86 Reported: 10 FEB 86

John Dolegoнski CH2M.HILL 1301 Dove Street, Suite 800 Newport Beach, California 92660

Project: N20391.B0

REPORT OF ANALYTICAL RESULTS

LOG HO	SAMPLE DESCRIPTION , SOIL SAMPLES		DATE SAMPLED
02-030-1	B-3-30	and then also also the time part part part and the time the time and time	03 FEB 86
PARAMETER		02-030-1	
Trichlorof Vinyl chlo cis-1,3-Di trans-1,3-	thylene, mg/kg luoromethane, mg/kg ride, mg/kg chloropropene, mg/kg Dichloropropene, mg/kg Method 8010, /kg	<pre><0.3 <0.3 <0.3 <0.3 <0.3 <0.3 <140</pre>	

Edward Hilson, Laboratory Director

Received: 03 FEB 86 Reported: 19 FEB 86

John Dolegowski CH2M.HILL 1301 Dove Street, Suite 800 Newport Beach, California 92660

Project: N20391.B0

LOG NO	SAMPLE DESCRIPTION , SOIL SAMPLES		DATE SAMPLED
02-037-1	B-3-50		03 FEB 86
PARAMETER		02-037-1	
	e by Infrared, mg/kg riority Pollutants	<10	
Extraction	•	02/14/86	
Acrolein,	nng/kg	∢ 3	
Acrylonitr	ile, mg/kg	. (3	
Other Pur	geable Priority Pollutants,	<0.3	

Received: 03 FEB 86 Reported: 19 FEB 86

John Dolegowski CH2M.HILL 1301 Dove Street, Suite 800 Newport Beach, California 92660

Project: N20391.BO

LOG NO	SAMPLE DESCRIPTION , SOIL S	AMPLES	DATE SAMPLED
02-037-3	B-3-70		03 FEB 86
PARAMETER		02-037-3	
Oil & Greas	e by Infrared, mg/kg riority Pollutants	<10	
Extraction	•	02/14/86	
Acrolein,	mg/kg	⟨3	
Acrylonitr		< 3	
Other Pur	geable Priority Pollutants,	(0.3	

Received: 03 FEB 86 Reported: 19 FEB 86

John Dolegowski CH2M.HILL 1301 Dove Street, Suite 800 Newport Beach, California 92660

Project: N20391.B0

LOG NO	SAMPLE DESCRIPTION	, SOIL SAMPLES		D	TE SAMPLED
02-037-4 02-037-5 02-037-6 02-037-7	B-3-10 B-3-20 B-3-60 B-3-40				03 FEB 86 03 FEB 86 03 FEB 86 03 FEB 86
PARAMETER		02-037-4	02-037-5	02-037-6	02-037-7
Sample Held	Not Analyzed	HOLD	HOLD	HOLD	HOLD

Received: 03 FEB 86 Reported: 19 FEB 86

John Dolegowski CHZM.HILL 1301 Dove Street, Suite 800 Newport Beach, California 92660

Project: N20391.B0

REPORT OF ANALYTICAL RESULTS

LOG NO	SAMPLE DESCRIPTION , SOIL SAMPLES		DATE SAMPLED
02-037-2	B-3-80		
PARAMETER		02-037-2	
Sample Held	, Not Analyzed	HOLD	

Edward Wilson, Laboratory Director

Results of laboratory analyses performed on the soil samples collected from the two borings are tabulated below. The laboratory report from Analytical Technologies, Inc. is included in Appendix B. In the laboratory report, a typographic error was made. The report states that the soil samples were analyzed for 1,1,1 - Tetrachloroethane (TCA). Upon receiving those results Gregg & associates, Inc. questioned ATI and found that a typographic error had been made and in fact the soil samples were analyzed for 1,1,1 Trichloroethane as requested. At the time this report was compiled, the corrected laboratory results report was not available, but will be forwarded when possible.

TABLE 1

BORING -	DEPTH (FEET)	CONCENTRATION OF	F 1,1,1-TRICHLOROETHANE (PPM) PPB
OTI-B-1	5, 10, 15, 20, 30, (composite)	, 40	0.7
OTI-B-2	5		6200
	10	1	2000
	15		^S 130
	20		150
	30	520	,000
	40		150

Analytical **Technologies,** Inc.

Corporate Offices: 225 W. 30th Street National City, CA 92050 619 477-417

ATI 1.D. 28301

October 17, 1985

Gregg & Associates
18351 Beach Blvd. Suite L
Huntington Beach, California 92634

Attention: Pat keating

Project No. : 85-154-001-

On October 9, 1985, Analytical Technologies, Inc. received sixteen (16) soil samples in good condition. Six (6) samples from boring B1 were composited into one sample. The composite and the samples from boring B2 were analyzed for 1,1,1-tetrachloroethane. (TCA).

The analysis of TCA was performed by gas chromatography/hall detector in accordance with EFA method BUTO.

The results of the ICA analysis were reported to Pat Assating on October 16, 1985, by Liz Shigley of ATL.

The results of the TCA analyses are enclosed and the results for the FCB's will be sent at a later date.

Train K. Augsburger Technical Associate

Since K. Augsbrugar

Reviewed by :

Laboratory Director

Note: The samples from this project will be disposed of thirty (Dir days from the date of this report unless we are inforced offerwise.

ANALYTICAL TECHNOLOGIES, INC. "

ATI 1.D. 28301

1,1,1- TETRACHLORDETHANE DATA SHEET

CLIENT: GREGG & ASSOCIATES

DATE RECEIVED: 10-9-85

DATE REPORTED: 10-17-85

FROJECT NO.: 85-154-001

SAMPLE MATRIX : SOIL METHOD : EPA 8010 DATE ANALYZED : 10-16-85 UNITS : ug/Kg

ati Apple	client Saffle	TCA	SURFLOGATE RECOVERY
1.0.	I.O.		•
5-10	BI COMPOSITE	€0 .7	72.8
11	£2-5'	\$200	92.7
12	5 2-10'	12000	107
13	£2-15'	130	75.2
14	\$2-20'	15ú	67.8
15	82-30	TWW	•
10	. B2-40'	150	56.1

[.] DIRECT INJECTION- NO SURROGATE ADDED.

DISTRIBUTION

4 copies to:

Ocean Technology, Inc. 2835 North Naomi Street Burbank, California 91504

Attention: Mr. Gene Palic

QUALITY CONTROL REVIEWER:

Donald W. Quigley, P. Principal Engineer

GJH/DAP/DWQ/slb